



## Value Wash

Aircraft Exterior Cleaner, Wet Wash

### DESCRIPTION

Celeste® Value Wash is a non-solvent based exterior wet wash for aircraft that effectively removes a wide range of soils allowing the aircraft to achieve better fuel efficiencies while extending the aircraft's paint life. Value Wash is a water-based exterior cleaner, making it both user and environmentally friendly. It has been formulated to function as a high performance cleaner, without being hazardous. Value Wash will have an aircraft surface looking shiny and will help to return the inherent shine like a waxed surface.

### THE REAL VALUE OF VALUE WASH

- **Increases Fuel Efficiencies** - the unique surfactant package in Value Wash is effective at removing a wide range of soils that if left untreated can increase the drag on the aircraft, requiring more fuel to be used
- **Extends Paint Life** - Value Wash helps to maintain a clean and smooth exterior, which helps minimize metal corrosion and locate leaks and local damage
- **Improved Appearance** - Value Wash leaves the surface looking shiny and helps to return the gloss and inherent shine like a just waxed surface
- **Cost Savings** - the adjustable dilution of Value Wash allows for efficient use of the product based on soil level
- **Environmentally Friendly and Safe** - Value Wash is formulated to be highly effective as well as safe for the environment and people to use.

### TEST REFERENCES

AMS 1526C  
Boeing D6-17487

### PROPERTIES

Flash Point	None
VOC	None
pH	10.00 - 11.00
Appearance	Colorless thin liquid
Storage	Cool, dry well-ventilated area; Avoid freezing
Shelf Life	36 months from date of manufacture

### DIRECTIONS

Light and medium Soil (recommended for routine use)	1:9 up to 1:19 (5% Concentration)	<b>Step 1: Apply diluted cleaner liberally to the soil area with a non-atomizing sprayer or with mops/brushes.</b> <b>Step 2: Allow sufficient time for soil attack and apply agitation with a mop/brush to dislodge the soil.</b> <b>Step 3: Rinse thoroughly with water.</b> <b>Note: Do not spray Value Wash in vents, pitot tubes, or nose of aircraft.</b>
Heavy Soil (Engineering Wash)	1:2 to 1:4	
Grease	Undiluted up to 1:3 (25% Concentration)	



SP-86000V/GAL

### FEATURES

- Non-aggressive, non-corrosive
- No flashpoint
- No volatile organic compounds (VOCs)
- Effective on a wide range of soils: bugs and organic compounds, grease and oil deposits, hydraulic fluid buildup, carbon buildup, general grime
- Easy rinsability
- Does not leave a dull or hazy film behind, even in hard water dilutions.
- Adjustable dilution, neat up to 1:19 depending on cleaning required, provides cost savings
- Returns gloss for a shinier surface
- Works in atomizing pressure sprayers
- Safe for routine use on light to medium soil, heavy soil, and grease
- Provides superior cleaning and less soil redeposition, making subsequent cleanings quicker and easier

*Contact your Celeste Account Representative for more information*

Celeste Part #	Description	Case Specification	Pallet Specification
SP-86000V/GAL	4 x gallon jugs per case	13 x 13 x 12 in, x 38 lbs (33 x 33 x 30 cm, x 17 kg)	27 cases x 3 layers, 57 in (145 cm) height
SP-86000V/5	5 gallon pail	12 x 10 x 15 in, x 46 lbs (30 x 25 x 38 cm, x 21 kg)	32 pails x 2 layers, 36 in (91 cm) height
SP-86000V/55	55 gallon drum	36 x 23 in, x 529 lbs (91 x 58 cm, x 240 kg)	4 drums x 1 layer, 42 in (107 cm) height