

D-5261NS



Product description:

CLEANER LUBRICANT PENETRANT

FEATURES:

- ▶ A special formulation of oil formulation that conforms to Mil-PRF-7870D.

KEY BENEFITS:

- ▶ Provides superior resistance to oxidation
- ▶ Ensures that parts, especially metals, do not rust
- ▶ Limits galvanic corrosion from occurring, especially on dissimilar metal assemblies
- ▶ **D-5261NS** can be used over temperatures from -65°F (-54°C) to 250°F (121°C)
- ▶ Prevents corrosion on metals
- ▶ A very effective cleaner and penetrating lubricant
- ▶ Penetrates tight parts (ie: heart strands of cables) and deposits a rust preventive lubricating film



SPECS:

- MIL-PRF-7870D (Oil used in **D-5261NS**)

APPLICATIONS:

- ✓ Available in bulk as **ZC-5261**

Rev: 29110D
11-30-2021

D-5261NS*Product description:***CLEANER LUBRICANT PENETRANT****APPLICATIONS:**

- ✓ **D-5261NS** can be used in conjunction with the **Formit**® extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the technical data sheet for more information.
- ✓ Use on aircraft flight controls, engine and landing gear cables, pulleys, pressure seals, cargo hoist cables, cargo restraining system components, door interlock actuating mechanisms, slide mechanisms, hinges, and static joints

PHYSICAL PROPERTIES:

- ▶ **Evaporation Rate:** Faster than ether
- ▶ **Flash Point of Oil:** 300°F (149°C)
- ▶ **Specific Gravity (H₂O=1):** 0.88
- ▶ **Temperature Range:** -65°F (-54°C) to 250°F (121°C)
- ▶ **Vapor Density:** Heavier than air
- ▶ **Viscosity @ 100°F (38°C):** Min. 10 cst.

AVAILABLE PACK SIZES:

- ▶ Case of 12 of 16 fl oz (473 ml) Aerosols-002056
- ▶ Case of 4 each Gallon (4 each of 3.8L) Cans-009425
- ▶ 5 Gallon (18.9L) Pail-002138
- ▶ Special Packaging Upon Request