



# Precision Clean

## Multi-Purpose Cleaner/Degreaser



### FEATURES

- Super industrial strength removes tough stains and soils
- Does not contain butyl, chlorinated or petroleum solvents, bleach, ammonia, or abrasives
- Alkaline formula inhibits flash rusting
- Rinses clean
- Safe of most surfaces (not for use with Magnesium & Aluminum)
- VOC compliant in all 50 states
- Nonfood Compounds Program Listed Category Code: C1 Registration #059854

### APPLICATIONS

- Bilges
- Carbon blocks
- Grease traps
- Exhaust hoods
- Compressors
- Concrete
- Engines
- Tanks
- Hoists
- Tools
- Machinery
- Garage floors
- Drill presses
- Sidewalks
- Driveways
- Ovens

### PACKAGING DETAILS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
02728	C02728	28 fl oz (828 mL)	trigger	12	27.0
02720	C02720	18 wt oz/510 g/525 mL	aerosol	12	18.0
02701	C02701	1 gal (3.78 L) - concentrate	bottle	4	38.0
02705	C02705	5 gal (18.93 L) - concentrate	pail	1	46.0
02755	C02755	55 gal (208 L) - concentrate	drum	1	535.0
02765	C02765	55 gal (208 L)	drum	1	535.0



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

**800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)**

LPS® is a registered trademark of Illinois Tool Works • All Rights Reserved



# Precision Clean

## Multi-Purpose Cleaner/Degreaser

PROPERTIES	AEROSOL	CONCENTRATE	RTU
Appearance/physical state	Gas/Aerosol	Clear/Liquid	Clear/Liquid
Odor	Citrus	Slight. Citrus.	Mild. Citrus.
Melting point/freezing point	Not available	Not available	Not available
Boiling point/range	200°F (93.33°C)	200°F (93.33°C)	200°F (93.33°C)
Vapor pressure	< 17.5 mm Hg @ 20°C	Not available	17.5 mm Hg @ 20°C (est.)
Partition coefficient	Not available	Not available	Not available
Percent volatile	Not available	Not available	96%
pH	12.7	13.4	12.7
Propellant	Petroleum Gases, Liquefied	Not applicable	Not applicable
VOC Content	5% (est.)	1.0% (est.)	<0.5% per Federal and State Consumer Product Regulations
Color	Clear Blue	Blue	Clear Blue
Flash point	Not established	>200°F (93.33°C)	>200°F (93.33°C)
Density	1.02 g/cm <sup>3</sup>	8.70 lb/gal	1.02 g/cm <sup>3</sup>
Evaporation rate	1 BuAc	Not available	1 BuAc
Vapor density	Not available	Heavier than air	>1
Auto-ignition temperature	Not available	Not available	Not available
Viscosity	< 3 cSt @ 25°C	Not available	Low viscosity comparable to water (water = 1 cSt @ 20°C)
Specific Gravity (water=1)	1.04	1.04	1.01
Temperature Range °F (°C)	Not available	Not available	Not available
Solubility in Water	100%	100%	100%

### DIRECTIONS

(Aerosol) Shake well before using. Spray directly on surface to be cleaned. Allow foam to set 10 to 30 seconds. Wipe or rinse clean. Conductive (water-based). Do not use on energized equipment. If equipment is still dirty or greasy, repeat procedure. (Bulk) KEEP FROM FREEZING. MIX WELL BEFORE USING. Rinse and/or wipe dry any residue. Test for compatibility on delicate materials.

Dilution Ratio Product:		
Water	Equipment	Applications
1: 4	Parts Washers	Carbon blocks, engines, exhaust hoods, forklifts, graffiti, marine, tanks, varnish
1: 5	Dip Tanks	Aviation, compressors, food processing equipment, floors, hoists, lifts, printing presses, tools
1: 7	Tumblers	Drill presses, oily parts, pulleys and wires
1: 10	Ultrasonic	Cleaning electrical parts (Deionized water rinse/dry)
1: 4-20	Steam Cleaner	Engines, parts
1: 60	Trigger Sprayer	Floors, leather and fabrics, tile, walls, wood
1: 40-80	Pressure Washer	Cleaning parts, floors, trucks, etc.
1: 100	Trigger Sprayer	Appliances, formica, general cleaning of glass, walls

### STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS)

### DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

**800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)**

LPS® is a registered trademark of Illinois Tool Works • All Rights Reserved