



Precision Clean

Multi-Purpose Cleaner/Degreaser



FEATURES

- Super industrial strength removes tough stains and soils
- Does not contain butyl, chlorinated or petroleum solvents, bleach, ammonia, or abrasives
- Alkaline formula inhibits flash rusting
- Rinses clean
- Safe of most surfaces (not for use with Magnesium & Aluminum)
- VOC compliant in all 50 states
- Nonfood Compounds Program Listed Category Code: C1 Registration #059854

APPLICATIONS

- Bilges
- Carbon blocks
- Grease traps
- Exhaust hoods
- Compressors
- Concrete
- Engines
- Tanks
- Hoists
- Tools
- Machinery
- Garage floors
- Drill presses
- Sidewalks
- Driveways
- Ovens

PACKAGING DETAILS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
02728	C02728	28 fl oz (828 mL)	trigger	12	27.0
02720	C02720	18 wt oz/510 g/525 mL	aerosol	12	18.0
02701	C02701	1 gal (3.78 L) - concentrate	bottle	4	38.0
02705	C02705	5 gal (18.93 L) - concentrate	pail	1	46.0
02755	C02755	55 gal (208 L) - concentrate	drum	1	535.0
02765	C02765	55 gal (208 L)	drum	1	535.0



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS® is a registered trademark of Illinois Tool Works • All Rights Reserved



Precision Clean

Multi-Purpose Cleaner/Degreaser

PROPERTIES	AEROSOL	CONCENTRATE	RTU
Appearance/physical state	Gas/Aerosol	Clear/Liquid	Clear/Liquid
Odor	Citrus	Slight. Citrus.	Mild. Citrus.
Melting point/freezing point	Not available	Not available	Not available
Boiling point/range	200°F (93.33°C)	200°F (93.33°C)	200°F (93.33°C)
Vapor pressure	< 17.5 mm Hg @ 20°C	Not available	17.5 mm Hg @ 20°C (est.)
Partition coefficient	Not available	Not available	Not available
Percent volatile	Not available	Not available	96%
pH	12.7	13.4	12.7
Propellant	Petroleum Gases, Liquefied	Not applicable	Not applicable
VOC Content	5% (est.)	1.0% (est.)	<0.5% per Federal and State Consumer Product Regulations
Color	Clear Blue	Blue	Clear Blue
Flash point	Not established	>200°F (93.33°C)	>200°F (93.33°C)
Density	1.02 g/cm ³	8.70 lb/gal	1.02 g/cm ³
Evaporation rate	1 BuAc	Not available	1 BuAc
Vapor density	Not available	Heavier than air	>1
Auto-ignition temperature	Not available	Not available	Not available
Viscosity	< 3 cSt @ 25°C	Not available	Low viscosity comparable to water (water = 1 cSt @ 20°C)
Specific Gravity (water=1)	1.04	1.04	1.01
Temperature Range °F (°C)	Not available	Not available	Not available
Solubility in Water	100%	100%	100%

DIRECTIONS

(Aerosol) Shake well before using. Spray directly on surface to be cleaned. Allow foam to set 10 to 30 seconds. Wipe or rinse clean. Conductive (water-based). Do not use on energized equipment. If equipment is still dirty or greasy, repeat procedure. (Bulk) KEEP FROM FREEZING. MIX WELL BEFORE USING. Rinse and/or wipe dry any residue. Test for compatibility on delicate materials.

Dilution Ratio Product:		
Water	Equipment	Applications
1: 4	Parts Washers	Carbon blocks, engines, exhaust hoods, forklifts, graffiti, marine, tanks, varnish
1: 5	Dip Tanks	Aviation, compressors, food processing equipment, floors, hoists, lifts, printing presses, tools
1: 7	Tumblers	Drill presses, oily parts, pulleys and wires
1: 10	Ultrasonic	Cleaning electrical parts (Deionized water rinse/dry)
1: 4-20	Steam Cleaner	Engines, parts
1: 60	Trigger Sprayer	Floors, leather and fabrics, tile, walls, wood
1: 40-80	Pressure Washer	Cleaning parts, floors, trucks, etc.
1: 100	Trigger Sprayer	Appliances, formica, general cleaning of glass, walls

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS)

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS® is a registered trademark of Illinois Tool Works • All Rights Reserved