



# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>LPS 3® (Bulk)</b>
<b>Other means of identification</b>	
<b>Part Number</b>	00322, 03128, 00305, 00355
<b>Recommended use</b>	A specialized soft-film coating designed to prevent rust and corrosion on steel, aluminum and other metals.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufacturer</b>	
<b>Manufacturer</b>	
<b>Company name</b>	ITW Pro Brands
<b>Address</b>	4647 Hugh Howell Rd. Tucker, GA 30084
<b>Country</b>	(U.S.A.) Tel: +1 770-243-8800
<b>In Case of Emergency</b>	1-800-424-9300 (inside U.S.) +001 703-527-3887 (outside U.S.)
<b>Website</b>	www.lpslabs.com
<b>E-mail</b>	lpssds@itwprobrands.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Flammable liquid and vapor. May be fatal if swallowed and enters airways.
<b>Precautionary statement</b>	
<b>Prevention</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection.
<b>Response</b>	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. In case of fire: Use appropriate media to extinguish.
<b>Storage</b>	Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None known.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreated Light		64742-47-8	60 - 70
Distillates Petroleum Hydrotreated Heavy		64742-54-7	1 - 10
1-butoxy-2-propanol		5131-66-8	1 - 5
Hydrodesulfurized Heavy Petroleum Naptha		64742-82-1	0.1 - 1

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable liquid and vapor.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
<b>Methods and materials for containment and cleaning up</b>	Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### U.S. - OSHA

Components	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	PEL	5 mg/m <sup>3</sup>	Oil mist
White Mineral Oil (CAS 8042-47-5)	TWA	5 mg/m <sup>3</sup>	Oil mist.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Xylene (CAS 1330-20-7)	PEL	435 mg/m <sup>3</sup> 100 ppm

#### ACGIH

Components	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m <sup>3</sup>	Oil mist
White Mineral Oil (CAS 8042-47-5)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

#### U.S. - NIOSH

Components	Type	Value	Form
White Mineral Oil (CAS 8042-47-5)	TWA	5 mg/m <sup>3</sup>	Mist.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Xylene (CAS 1330-20-7)	STEL	655 mg/m <sup>3</sup>
		150 ppm
	TWA	435 mg/m <sup>3</sup>
		100 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

<b>Appropriate engineering controls</b>	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
<b>Other</b>	Wear appropriate chemical resistant clothing.
<b>Respiratory protection</b>	In case of insufficient ventilation, wear suitable respiratory equipment. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Brown.
<b>Odor</b>	Mild. Cherry.
<b>Odor threshold</b>	Not Established
<b>pH</b>	Not Applicable
<b>Melting point/freezing point</b>	Not Established
<b>Initial boiling point and boiling range</b>	320 - 392 °F (160 - 200 °C)
<b>Flash point</b>	104.5 °F (40.3 °C) Tag Closed Cup
<b>Evaporation rate</b>	0.2 (butyl acetate = 1)
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	0.6 %
<b>Flammability limit - upper (%)</b>	6 %
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	2.6 mm Hg @ 20°C
<b>Vapor density</b>	4.8 (air = 1)
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble
<b>Partition coefficient (n-octanol/water)</b>	Not Established
<b>Auto-ignition temperature</b>	446 °F (230 °C) (concentrate)
<b>Decomposition temperature</b>	Not Established
<b>Viscosity</b>	20 - 550 cP
<b>Other information</b>	
<b>Density</b>	6.82

<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	78.45 %
<b>Specific gravity</b>	0.81 @ 20°C
<b>VOC</b>	75.58 % per U.S. State and Federal Consumer Product Regulations

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics**      Aspiration may cause pulmonary edema and pneumonitis.

### Information on toxicological effects

**Acute toxicity**      May be fatal if swallowed and enters airways.

Components	Species	Test Results
1-butoxy-2-propanol (CAS 5131-66-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	1400 mg/kg, 24 Hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 0.1 mg/l, 8 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Hydrodesulfurized Heavy Petroleum Naptha (CAS 64742-82-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
<b>Oral</b>		
LD50	Rat	4800 mg/kg

Components	Species	Test Results
Petrolatum (CAS 8009-03-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
White Mineral Oil (CAS 8042-47-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rat	2.2 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Xylene (CAS 1330-20-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	12000 mg/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rat	6400 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	3500 - 8600 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
<b>ACGIH Carcinogens</b>		
Xylene (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b>		
Not listed.		
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>		
Not listed.		
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful.	
<b>Further information</b>	None known.	
<b>12. Ecological information</b>		
<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	

Components	Species	Test Results
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
<b>Aquatic</b>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		2.9 mg/l, 96 hours
Xylene (CAS 1330-20-7)		
<b>Aquatic</b>		
Fish	LC50	Bluegill (Lepomis macrochirus)
		7.711 - 9.591 mg/l, 96 hours
<b>Persistence and degradability</b>	Not inherently biodegradable.	
<b>Bioaccumulative potential</b>		
<b>Partition coefficient n-octanol / water (log Kow)</b>		
Xylene		3.12 - 3.2
<b>Mobility in soil</b>	Not established.	
<b>Other adverse effects</b>	None known.	
<b>13. Disposal considerations</b>		
<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.	
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.	
<b>14. Transport information</b>		
<b>DOT</b>		
<b>UN number</b>	UN1268	
<b>UN proper shipping name</b>	Petroleum distillates, n.o.s. or Petroleum products, n.o.s. Mixture	
<b>Transport hazard class(es)</b>		
<b>Class</b>	3	
<b>Subsidiary risk</b>	-	
<b>Label(s)</b>	3	
<b>Packing group</b>	III	
<b>Special precautions for user</b>	Not available.	
<b>Special provisions</b>	144, B1, IB3, T4, TP1, TP29	
<b>Packaging exceptions</b>	150	
<b>Packaging non bulk</b>	203	
<b>Packaging bulk</b>	242	
<b>IATA</b>		
<b>UN number</b>	UN1268	
<b>UN proper shipping name</b>	Petroleum products, n.o.s. Mixture	
<b>Transport hazard class(es)</b>		
<b>Class</b>	3	
<b>Subsidiary risk</b>	-	
<b>Packing group</b>	III	
<b>Environmental hazards</b>	No.	
<b>ERG Code</b>	3L	
<b>Special precautions for user</b>	Not available.	
<b>Other information</b>		
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.	
<b>Cargo aircraft only</b>	Allowed with restrictions.	
<b>IMDG</b>		
<b>UN number</b>	UN1268	
<b>UN proper shipping name</b>	PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S. MIXTURE	

**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** III  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-E, S-E  
**Special precautions for user** Not available.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**DOT**



**IATA; IMDG**



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Toxic Substances Control Act (TSCA)

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Xylene (CAS 1330-20-7) Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
 Aspiration hazard

#### SARA 313 (TRI reporting)

Not regulated.



## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Xylene (CAS 1330-20-7)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

## US state regulations

### US. New Jersey Worker and Community Right-to-Know Act

Xylene (CAS 1330-20-7)

### California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7)

Hydrodesulfurized Heavy Petroleum Naptha (CAS 64742-82-1)

Petrolatum (CAS 8009-03-8)

Xylene (CAS 1330-20-7)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 06-08-2016

**Revision date** 11-01-2019

**Version #** 08

### Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### Revision information

Composition / Information on Ingredients: Disclosure Overrides  
Physical & Chemical Properties: Multiple Properties