



# All-Purpose Anti-Seize



## FEATURES

- Prevents seizure up to 1800°F (982°C)
- Moly fortified
- Lead free
- Not affected by contraction, expansion, or vibration
- Lowers friction; reduces wrench torque
- Protects against seizure, heat-freeze, galling, rust, and corrosion
- Will not run, drip, or settle out

## APPLICATIONS

- Fittings
- Flange Faces
- Gaskets
- Guides
- Keys
- Keyways
- Nuts & Bolts
- Slides

## PROPERTIES

<b>Appearance / Physical State</b>	paste/solid
<b>Odor</b>	Hydrocarbon-like
<b>Melting / Freezing Point</b>	500°F (260°C)
<b>Boiling Point / Range</b>	> 600.8°F (> 316°C)
<b>Vapor Pressure</b>	Not available
<b>Partition Coefficient</b>	Not available
<b>Percent volatile</b>	Not available
<b>Flammability</b>	Not available
<b>Propellant</b>	N/A
<b>VOC Content</b>	negligible
<b>Color</b>	dark gray
<b>Flash Point</b>	> 429.8°F (> 221.0°C)
<b>Density</b>	Not available
<b>Evaporation Rate</b>	Not available
<b>Vapor density</b>	Not available
<b>Auto-Ignition Temperature</b>	Not available
<b>Viscosity</b>	Not available
<b>Specific Gravity</b>	1.19
<b>Temperature Range</b>	- 65°F - 1800°F (-54°C - 982°C)
<b>4-Ball Weld Load</b>	500

## DIRECTIONS

Clean threaded surface thoroughly with wire brush. Apply thin coating of anti-seize to metal surface with brush provided or with bristle brush. Assemble as normal wiping off any excess. NOT FOR USE ON OXYGEN SYSTEMS.

## HANDLING

DO NOT handle, store, or open near an open flame, sources of heat, or sources of ignition. Protect material from direct sunlight. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Wear personal protective equipment. Avoid prolonged exposure. Avoid release to the environment.

## STORAGE

Keep away from heat, sparks, and open flame. Store in a well-ventilated place. Keep container tightly closed. Keep away from food, drink, and animal feeding-stuffs. Keep out of the reach of children. Use care in handling/storage.

## DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.

## AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
04108	C04108	0.5 lb / 227 grams	units	12	8 lbs
04110	C04110	1 lb / 454 grams	units	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustick®, Diamondkote®, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved