



# LPS<sup>®</sup> MAX NoFlash<sup>®</sup> 2.0

## Non-Flammable Contact Cleaner



### FEATURES

- Non-flammable, low VOC formula
- Fast evaporating
- Heavy-duty solvent cleaning power
- Does not contain harsh brominated solvents
- Leaves no residue
- Nozzle provides targeted or broad stroke application
- Contoured can for improved hand grip

### APPLICATIONS

- Contacts
- Controls
- Sensors
- Instrumentation
- Meters

### SPECIFICATIONS AND APPROVALS

- NSF International, K2

### PROPERTIES

<b>Appearance / Physical State</b>	Gas
<b>Color</b>	Clear
<b>Odor</b>	Ether-like.
<b>Melting / Freezing Point</b>	Not available.
<b>Boiling Point / Range</b>	< 131 °F (< 55 °C)
<b>Flash Point</b>	None
<b>Evaporation Rate</b>	Not available.
<b>Flammability</b>	Not available.
<b>Vapor Pressure</b>	Not available.
<b>Vapor Density</b>	Not available.
<b>Water Solubility</b>	Slight.
<b>Partition Coefficient</b>	Not available.
<b>Auto-Ignition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Density</b>	11.06
<b>Specific Gravity</b>	1.33
<b>VOC Content</b>	74%
<b>KB Value</b>	84
<b>Propellant</b>	HFO-1234ze, carbon dioxide
<b>Dielectric Strength</b>	43.1 kV

### HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### STORAGE

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage.

### DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
97416	12 wt oz / 340 g / 268 mL	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS<sup>®</sup>, SCRUBS<sup>®</sup>, DYKEM<sup>®</sup>, Accu-Lube<sup>®</sup>, DYMON<sup>®</sup>, Spray Nine<sup>®</sup>, and Cedar<sup>®</sup> are registered trademarks and Rustick<sup>™</sup>, Diamondkote<sup>™</sup>, and MetalMates<sup>™</sup> are trademarks of Illinois Tool Works • All Rights Reserved