

P/S 870 Class B corrosion inhibitive sealant

Surface preparation

Immediately before applying the sealant, the surface to be sealed must be clean, dry and free from loose material. The surface must be free from oil, grease, wax, dirt, dust, rust, scale, old sealant, and other contaminants. The surface must be free from laitance and other weak layers.

A roughness of 0.5mm profile depth is recommended. The surface must be free from laitance and other weak layers. The surface must be free from oil, grease, wax, dirt, dust, rust, scale, old sealant, and other contaminants. The surface must be free from laitance and other weak layers.

If a primer is used, it must be applied to the surface before the sealant is applied. The primer must be compatible with the sealant and the substrate.

Substrate moisture content must be less than 4%. Moisture content must be less than 4%. Moisture content must be less than 4%. Moisture content must be less than 4%.

For more detailed application instructions, please refer to the technical data sheet (TDS) and the application manual (AM) available from the manufacturer. Contact: 011 4000 1111 (toll-free) or 011 4000 1111 (toll-free).

Packing options

P/S 870 Class B is available in two pack and single pack options. The two pack option is available in 25kg and 50kg packs. The single pack option is available in 25kg and 50kg packs.

P/S 870 Class B is available in two pack and single pack options. The two pack option is available in 25kg and 50kg packs. The single pack option is available in 25kg and 50kg packs.

Storage life

The shelf life of P/S 870 Class B is 12 months from the date of manufacture. The shelf life of P/S 870 Class B is 12 months from the date of manufacture. The shelf life of P/S 870 Class B is 12 months from the date of manufacture.

The shelf life of P/S 870 Class B is 12 months from the date of manufacture. The shelf life of P/S 870 Class B is 12 months from the date of manufacture. The shelf life of P/S 870 Class B is 12 months from the date of manufacture.

ARE, Sanku, and Sanku are registered trademarks of P/S-Ca S&S India under all the registered with the U.S. Patent Office.

All other trademarks and registered trademarks are the property of their respective owners. The information provided in this document is for informational purposes only and does not constitute an offer of any product. The information provided in this document is for informational purposes only and does not constitute an offer of any product. The information provided in this document is for informational purposes only and does not constitute an offer of any product.

For more information, please contact us at info@ps-ca.com or call us at 011 4000 1111 (toll-free).

Health precautions

This product is a skin irritant. Avoid contact with skin. If contact occurs, wash immediately with water. Avoid contact with eyes. If contact occurs, flush immediately with water. Avoid contact with clothing. If contact occurs, remove clothing immediately. Avoid contact with food and drink. If contact occurs, wash immediately with water. Avoid contact with children and pets. If contact occurs, wash immediately with water.

For detailed use and safety information, please refer to the technical data sheet (TDS) and the application manual (AM) available from the manufacturer.

For emergency medical attention, call 1-800-455-5555.

Additional information is available from the manufacturer at www.ps-ca.com.

For sales and marketing information, call 1-800-455-5555 (1-800-455-5555).

PS-Ca S&S India Pvt. Ltd.
17005th Floor, 17005th Floor
Salmon, CA 94117
Tel: (916) 533-3333
Tel: (916) 533-3333
www.ps-ca.com

Page 1 of 1
© 2017 PS-Ca S&S India Pvt. Ltd.
P/S-Ca