



SAFETY DATA SHEET

1. Identification

Product identifier: SPRAYWAY GLASS CLEANER

Other means of identification

SDS number: RE1000000075

Recommended restrictions

Product use: Cleaner

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: Sprayway, Inc.
Address: 1000 INTEGRAM DR.
Pacific, MO 63069
Telephone: 1-630-628-3000
Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Gases under pressure

Compressed gas

Label Elements

Hazard Symbol:



Signal Word: Warning

Hazard Statement: Contains gas under pressure; may explode if heated.

Precautionary Statements

Storage: Protect from sunlight. Store in a well-ventilated place.

Hazard(s) not otherwise classified (HNOC): None.



3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Ethanol	64-17-5	1 - <5%
Ethanol, 2-butoxy-	111-76-2	1 - <5%
Propane	74-98-6	1 - <5%
Butane	106-97-8	1 - <5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** No data available.
- Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

- Treatment:** No data available.

5. Fire-fighting measures

- General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

- Specific hazards arising from the chemical:** Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

- Special fire fighting procedures:** No data available.



Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning up: Stop the flow of material, if this is without risk. Absorb with sand or other inert absorbent.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

7. Handling and storage

Precautions for safe handling: Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Protect from sunlight. Store in a cool place. Aerosol Level 1

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Ethanol	REL	1,000 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm 1,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (2009)
Ethanol, 2-butoxy-	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	REL	5 ppm 24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm 240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	25 ppm 120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Propane	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Morpholine	REL	20 ppm 70 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	30 ppm 105 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	20 ppm 70 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm 105 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)



	PEL	20 ppm	70 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
2-Propanol, 2-methyl-	STEL	150 ppm	450 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	300 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	100 ppm	300 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	150 ppm	450 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	100 ppm	300 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Silica	REL		6 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA		20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		6 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA		0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
2,6-Octadienal, 3,7-dimethyl- - Inhalable fraction and vapor.	TWA	5 ppm		US. ACGIH Threshold Limit Values (01 2010)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: No data available.

Other: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices.

9. Physical and chemical properties

Appearance

- Physical state:** liquid
- Form:** Spray Aerosol
- Color:** No data available.
- Odor:** No data available.
- Odor threshold:** No data available.
- pH:** 8.7 - 9.7
- Melting point/freezing point:** No data available.
- Initial boiling point and boiling range:** No data available.



Flash Point:	Not applicable
Evaporation rate:	No data available.
Flammability (solid, gas):	Non-flammable Aerosol
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	5,515 - 6,894 hPa (20 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.



Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: ATEmix: 36,844.23 mg/kg

Dermal
Product: ATEmix: 32,120.9 mg/kg

Inhalation
Product: ATEmix: 690.87 mg/l
ATEmix : 172.72 mg/l

Repeated dose toxicity
Product: No data available.

Specified substance(s):
Ethanol NOAEL (Rat(Male), Oral, 7 - 14 Weeks): 10 %(m) Oral Experimental result, Key study
Ethanol, 2-butoxy- NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key study
NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal Experimental result, Key study
Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):
Ethanol in vivo (Rabbit): Not irritant Experimental result, Key study
Ethanol, 2-butoxy- in vivo (Rabbit): Irritating Experimental result, Key study

Serious Eye Damage/Eye Irritation
Product: No data available.

Specified substance(s):
Ethanol Rabbit, 1 - 24 hrs: Not irritating
Ethanol, 2-butoxy- Rabbit, 24 - 72 hrs: Irritating

Respiratory or Skin Sensitization
Product: No data available.

Specified substance(s):
Ethanol Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol, 2-butoxy- Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity
Product: No data available.



IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Ethanol LC 50 (Pimephales promelas, 96 h): 15.3 g/l Experimental result, Key study

Ethanol, 2-butoxy- LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Ethanol LC 50 (Ceriodaphnia dubia, 48 h): 5,012 mg/l Experimental result, Key study

Ethanol, 2-butoxy- EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Ethanol NOAEL (Oryzias latipes): 7,900 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study

Ethanol, 2-butoxy- NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Ethanol LC 50 (Daphnia magna): 454 mg/l Experimental result, Key study
NOAEL (Daphnia magna): 9.6 mg/l Experimental result, Key study

Ethanol, 2-butoxy- EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study
EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Ethanol 95 % Detected in water. Experimental result, Key study

Ethanol, 2-butoxy- 90.4 % Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study
50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Ethanol Cyprinus carpio, Bioconcentration Factor (BCF): 4.5 Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Supporting study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.



Known or predicted distribution to environmental compartments

Ethanol	No data available.
Ethanol, 2-butoxy-	No data available.
Propane	No data available.
Butane	No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Wash before disposal. Dispose to controlled facilities.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, non-flammable
Transport Hazard Class(es)	
Class:	2.2
Label(s):	–
Packing Group:	II
Marine Pollutant:	No
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, non-flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	–
EmS No.:	
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, non-flammable
Transport Hazard Class(es):	
Class:	2.2
Label(s):	–
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.
Cargo aircraft only:	Allowed.



15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Ethanol	lbs. 100
Propane	lbs. 100
Butane	lbs. 100
Morpholine	lbs. 100
Nitrous acid, sodium salt (1:1)	lbs. 100
2-Propanol, 2-methyl-	lbs. 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Not listed.

SARA 302 Extremely Hazardous Substance
None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Ethanol	lbs. 100
Ethanol, 2-butoxy-	
Propane	lbs. 100
Butane	lbs. 100
Morpholine	lbs. 100
Nitrous acid, sodium salt (1:1)	lbs. 100
2-Propanol, 2-methyl-	lbs. 100

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Ethanol	10000 lbs
Ethanol, 2-butoxy-	10000 lbs
Propane	10000 lbs
Butane	10000 lbs
Morpholine	10000 lbs
Nitrous acid, sodium salt (1:1)	10000 lbs
2-Propanol, 2-methyl-	10000 lbs
Silica	10000 lbs
2,6-Octadienal, 3,7-dimethyl-	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Ethanol, 2-butoxy-	N230 lbs	N230 lbs.



Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)
US State Regulations**

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Ethanol
Ethanol, 2-butoxy-
Propane
Butane

US. Massachusetts RTK - Substance List

No ingredient regulated by MA Right-to-Know Law present.

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Ethanol
Ethanol, 2-butoxy-
Propane
Butane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable



Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Ontario Inventory:	On or in compliance with the inventory
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Japan (ENCS) List:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Mexico INSQ:	Not in compliance with the inventory.
New Zealand Inventory of Chemicals:	Not in compliance with the inventory.
Philippines PICCS:	Not in compliance with the inventory.
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.

16. Other information, including date of preparation or last revision

Issue Date:	03/18/2020
Revision Information:	No data available.
Version #:	2.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.