



Revision Number: 006.2

Issue date: 03/22/2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE C-MC 5884 AERO **IDH number:** 597177
Product type/use: Cleaners for Aeroplanes **Region:** United States
Restriction of Use: None identified **Contact information:**
Company address: Henkel Corporation Telephone: +1 (860) 571-5100
 Henkel Corporation MEDICAL EMERGENCY Phone: Poison Control Center
 One Henkel Way 1-877-671-4608 (toll free) or 1-303-592-1711
 Rocky Hill, Connecticut 06067 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: COMBUSTIBLE LIQUID.
 CAUSES SKIN IRRITATION.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 CAUSES SERIOUS EYE DAMAGE.
 CAUSES DAMAGE TO ORGANS.
 MAY CAUSE DAMAGE TO ORGANS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	2

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace.
Response: Wear protective gloves, eye protection, and face protection.
 IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center or physician. If exposed or concerned: Call a POISON CENTER/doctor/... If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Storage: Store in a well-ventilated place. Keep cool. Store locked up.
Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Solvent naphtha (petroleum), heavy arom. > 1% naphthalene	64742-94-5	30 - 60
Triethanolamine	102-71-6	5 - 10
2-Butoxyethanol	111-76-2	1 - 5
2-Methylpentane-2,4-diol	107-41-5	1 - 5
Naphthalene	91-20-3	1 - 5
Alkylphenol ethoxylate	9036-19-5	1 - 5
Alkylphenol ethoxylate	9036-19-5	1 - 5
Diethanolamine	111-42-2	1 - 5
Coconut fatty acid diethanolamide	68603-42-9	1 - 5
Benzotriazole	95-14-7	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If symptoms are experienced, remove source of contamination or move victim to fresh air. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	For skin contact flush with large amounts of water. Obtain medical attention if irritation persists.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. DO NOT induce vomiting unless directed to do so by medical personnel. Give one to two glasses of water or milk. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Symptoms:	See Section 11.
Notes to physician:	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Use media appropriate for surrounding material.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition.

Hazardous combustion products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Contain spill.

Clean-up methods:

Collect spilled material with an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Flush area with water to remove trace residue. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Keep container closed. Provide adequate ventilation. Wash thoroughly after handling. Keep away from heat, spark and flame. Do not cut or weld on empty drums. Sufficient vapors from residues may be present to cause explosion and serious injury and/or death.

Storage:

For safe storage, store between 40 °F (4.4 °C) and 100 °F (37.8 °C) Store in a cool, dry, well-ventilated area. Store away from strong oxidizers. Thaw and mix thoroughly if frozen.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Solvent naphtha (petroleum), heavy arom. > 1% naphthalene	(SKIN) (as total hydrocarbon vapor) Non-aerosol. 200 mg/m ³ TWA (as total hydrocarbon vapor) Non-aerosol.	None	None	None
Triethanolamine	5 mg/m ³ TWA	None	None	None
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m ³) PEL (SKIN)	None	None
2-Methylpentane-2,4-diol	10 mg/m ³ STEL Aerosol, inhalable. 50 ppm STEL Vapor fraction 25 ppm TWA Vapor fraction	None	None	None
Naphthalene	10 ppm TWA (SKIN)	10 ppm (50 mg/m ³) PEL	None	None
Alkylphenol ethoxylate	None	None	None	None
Alkylphenol ethoxylate	None	None	None	None
Diethanolamine	1 mg/m ³ TWA Inhalable fraction and vapor. (SKIN) Inhalable fraction and vapor.	None	None	None
Coconut fatty acid diethanolamide	None	None	None	None
Benzotriazole	None	None	None	None

Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
Respiratory protection:	If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.
Eye/face protection:	Wear chemical goggles; face shield (if splashing is possible).
Skin protection:	Chemical resistant, impermeable gloves. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Amber
Odor:	Solvent
Odor threshold:	Not available.
pH:	8.3 - 9.3
Vapor pressure:	Not determined
Boiling point/range:	> 100 °C (> 212°F)
Melting point/ range:	Not determined
Specific gravity:	0.96 - 0.98 at 23.9 °C (75.02 °F)
Vapor density:	Not determined
Flash point:	62.8 °C (145.04 °F) calculated
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not determined
Flammability:	Not applicable
Evaporation rate:	Not determined
Solubility in water:	Disperses in water as emulsion
Partition coefficient (n-octanol/water):	Not determined
VOC content:	405 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	This product may react with strong acids or oxidizing agents. Nitrites may react with organic amines to form nitrosamines which can cause cancer.
Reactivity:	Not available.
Conditions to avoid:	Avoid excessive heat and ignition sources.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes
-------------------------------------	------------------------

Potential Health Effects/Symptoms

Inhalation: This product is irritating to the respiratory system. Inhalation of high vapor concentrations may produce respiratory irritation, and may cause central nervous system (CNS) depression.

Skin contact: This product is irritating to the skin. Prolonged contact with this product may cause allergic skin sensitization reactions. A component in this product may be absorbed through the skin in harmful amounts.

Eye contact: Vapors irritate the eyes. Contact with liquid or mist will irritate the eyes.

Ingestion: Ingestion of this product may cause nausea, vomiting and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Solvent naphtha (petroleum), heavy arom. > 1% naphthalene	None	Irritant
Triethanolamine	Oral LD50 (Rat) = 8.0 g/kg Dermal LD50 (Rabbit) = > 20,000 mg/kg	Irritant, Allergen
2-Butoxyethanol	Oral LD50 (Rat) = 560 mg/kg Oral LD50 (Mouse) = 1.2 g/kg Oral LD50 (Rabbit) = 0.32 g/kg Oral LD50 (Rat) = 1.48 g/kg Oral LD50 (Mouse) = 1,519 mg/kg Dermal LD50 (Rabbit) = 400 mg/kg	Blood, Central nervous system, Irritant, Kidney, Liver
2-Methylpentane-2,4-diol	Oral LD50 (Rat) = 4.79 g/kg Oral LD50 (Mouse) = 3.5 g/kg	Irritant, Central nervous system
Naphthalene	Oral LD50 (Rat) = 490 mg/kg Oral LD50 (Rat) = 2.6 g/kg Oral LD50 (Rat) = 2,200 mg/kg Oral LD50 (Rat) = 2,400 mg/kg Dermal LD50 (Rat) = > 20 g/kg Dermal LD50 (Rabbit) = > 2.0 g/kg	Blood, Central nervous system, Eyes, Irritant
Alkylphenol ethoxylate	None	Irritant
Alkylphenol ethoxylate	None	Irritant
Diethanolamine	Oral LD50 (Rat) = 710 mg/kg Oral LD50 (Rat) = 1.82 g/kg	Allergen, Corrosive, Irritant, Liver, Respiratory
Coconut fatty acid diethanolamide	Oral LD50 (Rat) = 12,200 mg/kg Oral LD50 (Rat) = > 5,000 mg/kg	Allergen, Irritant, Kidney, Skin, Some evidence of carcinogenicity, Thyroid
Benzotriazole	Oral LD50 (Rat) = 600 mg/kg Oral LD50 (Mouse) = 615 mg/kg	Irritant, Central nervous system

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Solvent naphtha (petroleum), heavy arom. > 1% naphthalene	No	No	No
Triethanolamine	No	No	No
2-Butoxyethanol	No	No	No
2-Methylpentane-2,4-diol	No	No	No
Naphthalene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Alkylphenol ethoxylate	No	No	No
Alkylphenol ethoxylate	No	No	No
Diethanolamine	No	Group 2B	No
Coconut fatty acid diethanolamide	No	Group 2B	No
Benzotriazole	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal. This product contains a alkylphenol or nonylphenol ethoxylate.
Hazardous waste number:	Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Combustible liquid, n.o.s. (Petroleum distillates)
Hazard class or division:	Combustible Liquid
Identification number:	NA 1993
Packing group:	III

International Air Transportation (ICAO/IATA)

Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Petroleum distillates)
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III

Water Transportation (IMO/IMDG)

Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Petroleum distillates)
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III
Marine pollutant:	Petroleum distillates
Exceptions:	Classified per IMDG Amendment 34; Effective Jan 1, 2010.

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 2-Butoxyethanol (CAS# 111-76-2). Naphthalene (CAS# 91-20-3). Diethanolamine (CAS# 111-42-2).
CERCLA Reportable quantity:	Naphthalene (CAS# 91-20-3) 100 lbs. (45.4 kg) Diethanolamine (CAS# 111-42-2) 100 lbs. (45.4 kg)
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Additional Regulatory Information: This product is controlled for export by the United States Department of Commerce. The Export Classification Control Number (ECCN) is 1C995.a.2.a

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date: 03/22/2019

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.