

Revision Date: 01/05/2023

1. Identification

1.1. Product identifier

Product Identity SO-SURE Zinc Chromate Aerosol Primer

Alternate Names Specification: TT-1757B, Type II, Class C, Color T

Color Number 34151)

LHB Part Number: 0084---348

National Stock Number: 8010-00-899-8825

CAGE Code: 0FTT5 and 1A864 Contract Number: SPE8EG-16-D-0015

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Product Label

1.3. Details of the supplier of the safety data sheet

Company Name LHB Industries

8833 Fleischer Place Berkeley, MO 63134

Emergency

24 hour Emergency Telephone No. (800) 633-8253 (PERS)

Customer Service: LHB Industries (314) 423-4333

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222 Extremely flammable aerosol.

Press. Gas;H280 Contains gas under pressure; may explode if heated.

Eye Dam. 2A;H319 Causes serious eye irritation.

Skin Sens. 1;H317 May cause an allergic skin reaction.

Resp. Sens. 1;H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled.

Carc. 1A;H350 May cause cancer.

STOT SE 3;H336 May cause drowsiness or dizziness.

Asp. Tox. 1;H304 May be fatal if swallowed and enters airways.

Aguatic Acute 3;H402 Harmful to aguatic life.

Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.



Revision Date: 01/05/2023

2.2. Label elements



Danger

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness and dizziness.

H350 May cause cancer.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

May displace oxygen and cause rapid suffocation.

Pressurized container: May burst if heated.

[Prevention]

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust, fume, gas, mist, vapors, spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, face protection.

[Response]

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice or attention.

P311 Call a POISON CENTER or doctor, physician.

P331 Do NOT induce vomiting.



Revision Date: 01/05/2023

P333+313 If skin irritation or a rash occurs: Get medical advice or attention.

P337+313 If eye irritation persists: Get medical advice or attention.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER, doctor or physician.

P362 Take off contaminated clothing and wash before reuse.

[Storage]

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C , 122 °F.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes	
Acetone CAS Number: 0000067-64-1	25 - 50	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336		
Acetic acid, methyl ester CAS Number: 0000079-20-9	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336		
Propane CAS Number: 0000074-98-6	10 - 25	Flam. Gas 1;H220		
Zinc chromate < Zinc chromate hydroxide > CAS Number: 0013530-65-9	5 - 10	Skin Sens. 1;H317 Resp. Sens. 1;H334 Carc. 1A;H350		
Butane CAS Number: 0000106-97-8	5 - 10	Flam. Gas 1;H220		
Naphtha (petroleum), hydrotreated light CAS Number: 0064742-49-0	5 - 10	Asp. Tox. 1;H304		
Isobutane CAS Number: 0000075-28-5	1 - 5	Flam. Gas 1;H220 Press. Gas;H280		
N-Butyl Acetate CAS Number: 0000123-86-4	1 - 5	Flam. Liq. 3;H226 STOT SE 3;H336		
Stoddard solvent CAS Number: 0008052-41-3	0.10 - 1.0	STOT RE 1;H372 Asp. Tox. 1;H304		

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

^{*}PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.



Revision Date: 01/05/2023

Section 4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious, place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce

vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview EFFECTS OF OVEREXPOSURE: Overexposure may result in light-headedness,

staggering gait, giddiness, and possible nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause eye and skin irritation. SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure. MEDICAL CONDITIONS AGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, and eye disorders. Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

Treat symptomatically. Check section 2.2 (GHS Label Elements) for further details.

Inhalation May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. May

cause allergy or asthma symptoms of breathing difficulties if inhaled.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO², powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust, fume, gas, mist, vapors, spray.



Revision Date: 01/05/2023

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. 126

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]

7.2. Conditions for safe storage, including any incompatibilities

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Strong acids and oxidizing materials

Check section 2.2 (GHS Label Elements) for further details. - [Storage]

7.3. Specific end use(s)

No data available.



Revision Date: 01/05/2023

Section 8. Exposure controls / personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value		
0000067-64-1 Acetone	Acetone	OSHA	TWA 1000 ppm (2400 mg/m³) STEL 2400 mg/m³		
		ACGIH	TWA: 500 ppm STEL: 750 ppm		
		NIOSH	250 ppm (590 mg/m³) TWA		
0000074-98-6	Propane	OSHA	TWA 1000 ppm (1800 mg/m³)		
		ACGIH	Ensure Minimal Oxygen Content (ACGIH appendix F)		
		NIOSH	TWA 1000 ppm (1800 mg/m³)		
0000075-28-5	Isobutane	OSHA	No Established Limit		
		ACGIH	1000 ppm STEL (explosion hazard, listed under Butane, isomers)		
		NIOSH	TWA 800 ppm (1900 mg/m³)		
0000079-20-9	Acetic acid, methyl ester	OSHA	TWA 200 ppm (610 mg/m³)		
		ACGIH	TWA: 200 ppm STEL: 250 ppm		
		NIOSH	TWA 200 ppm (610 mg/m³) STEL: 250 ppm (760 mg/m³)		
0000106-97-8	Butane	OSHA	No Established Limit		
		ACGIH	TWA: 600 ppm STEL: 750 ppm		
		NIOSH	TWA 800 ppm (1900 mg/m³)		
0000123-86-4	N-Butyl Acetate	OSHA	TWA 150 ppm (710 mg/m ³		
		ACGIH	TWA: 150 ppm, STEL 200 ppm		
		NIOSH	TWA 150 ppm (710 mg/m³) STEL: 200 ppm (950 mg/m³)		
0008052-41-3	Stoddard solvent	OSHA	TWA 500 ppm (2900 mg/m³)		
		ACGIH	TWA: 290 mg/m³ STEL: 580 mg/m³		
		NIOSH	TWA 350 mg/m³ C 1800 mg/m³ [15-minute]		
0013530-65-9	Zinc chromate < Zinc chromate hydroxide >	OSHA	0.005 mg/m³ TWA, 0.0025 mg/m³ 1 mg/m³ PEL (as Cr)		
		ACGIH	TWA: 0.01 mg/m³ (as Cr)		
		NIOSH	No Established Limit		
0064742-49-0	Naphtha (petroleum), hydrotreated light	OSHA	No Established Limit		
		ACGIH	No Established Limit		
		NIOSH	No Established Limit		

8.2. Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit, they must use the

appropriate, certified respirators.

Eyes Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the

splash of liquids.

Skin Overalls which cover the body, arms and legs should be worn. Skin should not be exposed.

All parts of the body should be washed after contact.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to



Revision Date: 01/05/2023

maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Color: Green Liquid gas Physical State: Liquid/Gas

Odor Solvent/Paint **Odor threshold** Not determined pН Not Determined **Melting point / freezing point** Not Determined Initial boiling point and boiling range Not Determined **Flash Point** Propellant < 0 F **Evaporation rate (Ether = 1)** Not Determined Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Determined

Upper Explosive Limit: Not Determined

Vapor pressure (Pa) Not Determined **Vapor Density** Not Determined **Relative Density** 0.784 (6.54 lb/gal)

Solubility in Water Insoluble Partition coefficient n-octanol/water (Log Kow) Not Measured **Auto-ignition temperature** Not Determined **Decomposition temperature** Not Determined Viscosity (cSt) Not Determined **VOC Content** 312 g/L (2.60 lb/gal)

% Volatile (by volume) 0.0 0.0 HAPS (lbs/gal) HAPS (lbs/gal of Solids) 0.0 HAPS (lbs/lb of Solids) 0.0 0.48 **Maximum Incremental Reactivity**

9.2. Other information

No other relevant information.



Revision Date: 01/05/2023

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Do not expose to heat or store at temperature above 120°F.

10.5. Incompatible materials

Strong acids and oxidizing materials

10.6. Hazardous decomposition products

Oxides of Carbon

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Rabbit - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available
Acetic acid, methyl ester - (79-20-9)	6,482.00, Rat - Category: NA	> 2,000.00, Rat - Category: NA	No data available	73.80, Rabbit - Category: NA	No data available
Propane - (74-98-6)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Zinc chromate < Zinc chromate hydroxide > - (13530-65-9)	No data available	No data available	No data available	No data available	No data available
Butane - (106-97-8)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Naphtha (petroleum), hydrotreated light - (64742-49-0)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available	No data available	No data available
Isobutane - (75-28-5)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
N-Butyl Acetate - (123-86-4)	10,760.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available	No data available



Revision Date: 01/05/2023

Stoddard solvent - (8052-41-3)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.50, Rat - Category: NA	No data available
--------------------------------	--------------------------------------	----------------------	----------------------	-----------------------------	----------------------

Carcinogen Data

CAS No.	Ingredient	Source	Value		
0000067-64-1	Acetone	OSHA	Regulated Carcinogen: No;		
		NTP	Known: No;	Suspected: No;	
		IARC	Group 1: No;	Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	A4		
0000074-98-6	Propane	OSHA	Regulated Ca	arcinogen: No;	
		NTP	Known: No;	Suspected: No;	
		IARC	Group 1: No;	Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	No Establishe	ed Limit	
0000075-28-5	Isobutane	OSHA	Regulated Carcinogen: No;		
		NTP	Known: No; Suspected: No;		
		IARC	Group 1: No;	Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	No Establishe	ed Limit	
0000079-20-9	Acetic acid, methyl ester	OSHA	Regulated Ca	arcinogen: No;	
		NTP	Known: No;	Suspected: No;	
		IARC	Group 1: No;	Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	No Establishe	ed Limit	
0000106-97-8	Butane	OSHA	Regulated Carcinogen: No;		
		NTP	Known: No; Suspected: No;		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
0000123-86-4	N-Butyl Acetate	OSHA	Regulated Carcinogen: No;		
		NTP	Known: No; Suspected: No;		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Establishe	ed Limit	
0008052-41-3	Stoddard solvent	OSHA	Regulated Ca	arcinogen: No;	
		NTP	Known: No;	Suspected: No;	
		IARC	Group 1: No;	Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	No Established Limit		
0013530-65-9	Zinc chromate < Zinc chromate	OSHA	Regulated Carcinogen: Yes;		
	hydroxide>	NTP	Known: Yes;	Suspected: No;	
		IARC	Group 1: Yes	; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	No Established Limit		
0064742-49-0	Naphtha (petroleum), hydrotreated light	OSHA	Regulated Carcinogen: No;		
		NTP	Known: No; Suspected: No;		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
Classification		Ca	tegory	Hazard Description	
Acute toxicity (oral)		_ -	J - J	Not Applicable	



Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	1	May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity		Not Applicable
Carcinogenicity	1A	May cause cancer.
Reproductive toxicity		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard	1	May be fatal if swallowed and enters airways.

Section 12. Ecological information

12.1. Toxicity

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Acetone - (67-64-1)	8,120.00, Pimephales promelas	8,800.00, Daphnia pulex	7,000.00 (96 hr), Pseudokirchneriella subcapitata
Acetic acid, methyl ester - (79-20-9)	300.00, Danio rerio	1,026.70, Daphnia magna	> 120.00 (72 hr), Desmodesmus subspicatus
Propane - (74-98-6)	49.90, Fish	69.43, Daphnia sp	19.37 (72 hr), Algae
Zinc chromate < Zinc chromate hydroxide > - (13530-65-9)	Not Available	Not Available	Not Available
Butane - (106-97-8)	49.90, Fish (Piscis)	69.43, Daphnia sp	19.37 (96 hr), Algae
Naphtha (petroleum), hydrotreated light - (64742-49-0)	Not Available	2.60, Chaetogammarus marinus	Not Available
Isobutane - (75-28-5)	Not Available	Not Available	Not Available
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	44.00, Daphnia sp	246.00 (72 hr), Pseudokirchnerella subcapitata
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.



Revision Date: 01/05/2023

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state, and local regulations when disposing of this substance.

Section 14. Transport information

DOT (Domestic Surface IMO / IMDG (Ocean ICAO/IATA Transportation) Transportation)

14.1. UN number UN1950 UN1950 UN1950

14.2. UN proper shipping UN1950, Aerosols, Limited Aerosols, Limited Quantity Aerosols, Limited name Quantity, 2.1,

Quantity

14.3. Transport hazard **DOT Hazard Class: 2.1 IMDG**: 2.1 Air Class: 2.1 Sub Class: Not Applicable Sub Class: Not Applicable Sub Class: Not class(es)

Applicable

14.4. Packing group Not Applicable Not Applicable Not Applicable

14.5. Environmental hazards

Marine Pollutant: No;

14.6. Special precautions for user

Not Applicable

Section 15. Regulatory information

The regulatory data in Section 15 is not intended to be all-inclusive, only selected **Regulatory Overview**

regulations are represented.

Toxic Substance All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

EPCRA 302 Extremely Hazardous: To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Revision Date: 01/05/2023

EPCRA 313 Toxic Chemicals:

Zinc chromate < Zinc chromate hydroxide >

Proposition 65 - Carcinogens (>0.0%):

Zinc chromate < Zinc chromate hydroxide >

Proposition 65 - Developmental Toxins (>0.0%):

Zinc chromate < Zinc chromate hydroxide >

Proposition 65 - Female Repro Toxins (>0.0%):

Zinc chromate < Zinc chromate hydroxide >

Proposition 65 - Male Repro Toxins (>0.0%):

Zinc chromate < Zinc chromate hydroxide >

Proposition 65 Label Warning:



WARNING: This product can expose you to chemicals including [Zinc chromate < Zinc chromate hydroxide >], which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA Ranking



HMIS RATING			
Health :	3		
Flammability :	3		
Reactivity:	0		
Personal Protection :	Н		

Section 16. Other information

Revision Date 01/05/2023

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.



Revision Date: 01/05/2023

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document