Polyken 290FR PE Coated Fiberglass Cargo Pit Sealing Tape

Product Information Sheet

SKU/Product ID/Reference

290FR

Product Description

PE Coated Fiberglass Cargo Pit Sealing Tape



Features and Benefits

- Coated Fiberglass Cloth
 - Super high tensile strength
 - Resists flame penetration for added safety
 - High moisture resistance
 - Coating protects skin from contacting fiberglass
- Rubber Based Adhesive
 - Aggressive adhesion to all surfaces
 - Maintains seal under heavy loads
 - Resists flagging and lifting
 - Deca-BDE Free

Regions Available

Global



Product Information	
Adhesive Type	Rubber
Carrier / Support / Facestock	Cloth
Gauge / Mil	13.0 mil
OEM / Specification Body & Specification	AIRBUS > ABD0031, Paragraphs 7.3.2 AIRBUS > ABD0031, Paragraphs 7.4 Boeing > 737-SL-25-085-B Boeing > 737-SL-25-115-B Boeing > 747-SL-25-195-B Boeing > 767-SL-25-112-B Boeing > 777-SL-25-037-B Bombardier/deHavilland > DSC 91-8-2 Bombardier/deHavilland > DSC 91-8-2A FAA > FAR 25.853(a) FAA > FAR 25.855(d)
Operating Temp Range	40 to 200 °F
Performance Category / Characteristics	Moisture/Water Resistance
Color(s)	Custom Color
Custom color(s)	White - Printed
Product Construction	Single-Coated Tape
Weight per Square Yard (oz/sy)	13.4 oz/sy

berryglobal.com

Specifications are subject to change without notice.

